

SOLISTA LX CEILING LED BEACON

Alarm devices
Product Datasheet

EN 54-23 Coverage Reference: C-3-7.5

Features

- Ultra low current consumption
- Up to 7.5m coverage (132m³)
- 0.5Hz or 1Hz Flash rate
- Use where current consumption is a key consideration
- Ideal for bedrooms, bathrooms and toilets
- Switch flash rate to 0.5Hz to reduce current consumption
- Reduces power consumption by up to 50%



Description / Application

The Solista LX Ceiling has a unique lens design that distributes the light in a cylindrical shape, to achieve the required illumination specified by EN 54-23. Designed for installation at a height of up to 3m and with a discrete appearance, the device is ideal for a variety of applications.

Product Name	Part number	Description
Solista LX Ceiling LED beacon	116-4340-007.0002	Solista LX conventional beacon, Ceiling mounted, shallow base

Technical specifications	
Mounting Type	Ceiling
Voltage	9 – 60VDC
Current	10 – 25mA dependent on setting
Coverage (y)	7.5m (Switchable to 3m)
Mounting Height (x)	3m (max)
Coverage Volume Code	C-3-7.5
Coverage Volume	132m ³ (21m ³)
Flash Rate	1Hz (Switchable to 0.5Hz)
Operating Temperature	-25°C - +70°C
Monitoring	Reverse Polarity
Protection	IP33C Shallow Base
Weight	100g
Body Colour	White
Flash Colour	Red

Dimension Drawing

