

### **Ultraviolet Test Lamp W8066**



#### **DESCRIPTION**

The W8066 Ultraviolet (UV) Test Lamp is a portable, battery operated source of UV radiation that is used for periodic testing of ultraviolet flame detection systems. The intrinsically safe device simulates a fire by producing a beam of UV radiation with the same wavelength as the response range of Det-Tronics UV detectors, enabling the operator to verify proper system operation without the need for an open flame. The physical characteristics of the W8066 are comparable to a common flashlight, making it easier to handle and operate than other test lamps.

#### **SPECIFICATIONS**

##### **OPERATING RANGE—**

The ultraviolet test lamp will typically actuate a UV detection system (using a DE1888 sensor tube) at a distance of approximately 30 feet (10 meters) from the detector, with the system sensitivity level set at 25 cps.

##### **ENCLOSURE—**

CSA certified intrinsically safe for use in outdoor hazardous locations, Class I, Division 1, Groups A, B, C, D; Class II, Division 1, Group G; T4A. FM approved intrinsically safe for Class I, Division 1, Groups A, B, C, D; T4A. Designed to meet BASEEFA/CENELEC requirements for EEx ia IIC T4.

##### **INPUT POWER—**

The W8066 test lamp is powered by a 9 volt alkaline battery.

##### **TEMPERATURE RATINGS—**

Operating: 32°F to 104°F (0°C to 40°C).  
Storage: -22°F to 158°F (-30°C to 70°C).

##### **OPERATING TIME—**

Approximately four hours continuous operation between battery replacement. This will vary with the ambient temperature.

##### **SHIPPING WEIGHT—**

1.1 pound (0.5 kg).

## Ultraviolet/Infrared Test Lamp W867



### DESCRIPTION

The W867 Ultraviolet/Infrared (UV/IR) Test Lamp is a portable, battery operated, explosion-proof source of UV and IR radiation that is used for periodic testing of UV, IR or UV/IR flame detection systems. The W867 Test Lamp simulates a fire by producing UV and IR radiation with the same frequency and wavelength as the response range of Det-Tronics UV/IR detectors, enabling the operator to verify proper system operation without the need for an open flame.

### SPECIFICATIONS

#### ENCLOSURE—

Explosion proof cast aluminum housing is FM approved for Class I, Division 1, Groups C and D; Class II, Division 1, Groups E, F, and G; T6.

#### ELECTRICAL RATINGS—

Battery Charger Input Voltage: 120 vac, 60 hz; 220 vac, 50 hz optional.

#### TEMPERATURE RATINGS—

Operating:  $-5^{\circ}\text{F}$  to  $+122^{\circ}\text{F}$  ( $-15^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$ ).  
Charge:  $32^{\circ}\text{F}$  to  $104^{\circ}\text{F}$  ( $0^{\circ}$  to  $40^{\circ}\text{C}$ ).  
Storage:  $-5^{\circ}\text{F}$  to  $+104^{\circ}\text{F}$  ( $-15^{\circ}\text{C}$  to  $+40^{\circ}\text{C}$ ).

#### OPERATING TIME—

Approximately 15 minutes continuous between re-charges. This will vary with the ambient temperature.

#### SHIPPING WEIGHT—

14 pounds.

## Dual Frequency Infrared Test Lamp W868



### DESCRIPTION

The W868 Dual Frequency Infrared (IR) Test Lamp is a portable, battery operated source of IR radiation that is used for periodic testing of dual frequency infrared flame detection systems. The W868 simulates a fire by producing pulsing infrared radiation with the same frequency and wavelength as the response range of Det-Tronics dual frequency IR detectors, enabling the operator to verify proper system operation without the need for an open flame.

### SPECIFICATIONS

#### ELECTRICAL RATINGS—

The W868 test lamp is powered by a four "D" cell 1.5 volt alkaline batteries, 0.25 ohm maximum internal resistance each cell.

#### TEMPERATURE RATINGS—

Operating:  $32^{\circ}\text{F}$  to  $140^{\circ}\text{F}$  ( $0^{\circ}\text{C}$  to  $60^{\circ}\text{C}$ ).  
Storage:  $-13^{\circ}\text{F}$  to  $158^{\circ}\text{F}$  ( $-25^{\circ}$  to  $70^{\circ}\text{C}$ ).

#### OPERATING TIME—

Approximately two hours continuous between battery replacement. This will vary with the ambient temperature.

#### SHIPPING WEIGHT—

2 pounds.



### Detector Electronics Corporation

6901 West 110th Street • Minneapolis, Minnesota 55438 USA • Facsimile (612) 829-8750  
Telephone (612) 941-5665 or (800) 765-FIRE • Telex 6879043 DETEL UW • Cable Detronics  
Printed in USA