

Horn speaker - BBR-DK-15/T PP

Voice alarm system
Product datasheet

Horn speaker

Powerful horn speaker for voice alarm. Equipped with ceramic terminal block, thermal fuse and a temperature resistant cable, providing increased security in case of a fire.

BBR-DK-15/T PP is approved according to EN 54-24:2008. The horn speakers of the DK series are particularly applicable for the reproduction of announcements and warnings. Due to their excellent capability and enormous sound pressure they are perfectly suitable for indoor as well as for outdoor use. The model with 2 cable glands allows to loop in loop out the cabling. This avoids the need for an additional junction box.



Technical specifications	
Certification	EN 54-24:2008
Loading rate	15 Watt
Frequency range (-10 dB)	460 — 9 000 Hz
SPL 1 W / 1 m	108 dB
SPL Pmax / 1 m	120 dB
Radiation angle 1.000 Hz (-10 dB)	120°
Transformer	100 V, 15/7,5/3,75/1,87 Watt
Dimensions	Ø208 x 272 mm
Weight	1,9 kg
Material	ABS plastic housing
Connection	3-pole ceramic clamp
Colour	RAL 7035 Grey
Protection	IP66

Part number	Description
116-BBR-DK-15/T PP	HORNSPEAKER 15W DK-15/T EN 54

AUTRONICA FIRE AND SECURITY AS

Head office, Trondheim, NO-7483 Norway Tel: +47 73 58 25 00, fax: +47 73 58 25 01, e-mail: info@autronicafire.no

Oil and Gas division, Stavanger, Norway Tel: +47 51 84 09 00, fax: +47 51 84 09 99

Maritime division, Spikkestad, Norway Tel: +47 31 29 55 00, fax: +47 31 29 55 01

Visit Autronica Fire and Security AS' website: www.autronicafire.com