

# ROLP LX WALL BASE

Alarm devices

Product Datasheet

EN 54-23 Coverage Reference: W-2.4-7.5

## Features

- Ultra low current consumption
- RoLP sounder options
- Up to 7.5m coverage (135m<sup>3</sup>) - switchable to 2.5m
- 0.5 or 1Hz flash rate
- Use where current consumption is a key consideration
- Ideal for bedrooms, bathrooms and toilets
- Switch flash rate to 0.5Hz to reduce current consumption

## Description / Application

The RoLP LX Wall base is ideal for dual use applications where a visual alarm device is required in addition to an audible alarm. Recommended for wall use and requiring just one installation point, the RoLP LX Wall base is available to use with standard RoLP sounder.



The photo shows the complete product, including both the base and sounder.

Product Name	Part number	Description
RoLP LX Wall base	116-4340-007.0003	RoLP LX Wall base
Roshni LP	116-7770-009.0002	

Technical specifications (for complete product; wall base and sounder)	
Mounting Type	Wall
Voltage	18 – 28VDC (Fire Use) 9 - 15 VDC (Fire Use)
Current	22 – 37mA dependent on setting (Sounder and beacon; tone 3)
Coverage (y)	7.5m (Switchable to 2.5m)
Mounting Height (x)	2.4m (max)
Coverage Volume Code	W-2.4-7.5
Coverage Volume	135m <sup>3</sup> (15m <sup>3</sup> )
Flash Rate	1Hz (Switchable to 0.5Hz)
Operating Temperature	-25°C - +70°C
Monitoring	Reverse Polarity
Protection	IP65
Weight	200g
Body Colour	Red
Flash Colour	Red
Sound Output	102dB(A) (Typical tone 3 – RoLP)

### Dimension Drawing (complete product; wall base and sounder)

