## Certificate No.: 8504-UKCA-CPR-UKCSP10118



## **C**ERTIFICATE OF CONSTANCY OF PERFORMANCE

Issued by DBI Certification-UK, approved body No. 8504.

In compliance with UK STATUTORY INSTRUMENT 2020 No. 1359 Construction Products Regulation 2011 (retained EU law EUR 305/2011) as amended by the Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and the Construction Products (Amendment etc.) (EU Exit) Regulations 2020, this certificate applies to the construction product

V-100,	V-110,	V-120
--------	--------	-------

The product fulfils the essential characteristic:

	See	Annex 1			
Intended use	: App	lications rela	ted to auto	omatic fire ala	arm systems
Placed on the	e market under the name or tra	de mark of:			
	Autr	onica Fire an	d Security	AS	
	Bron	nstadvegen 5	59		
	NO-7	7047 Trondho	eim		
	Norv	vay			
and produce	d in the manufacturing plant:				
	СРА:	10058			
This attests t	hat all provisions concerning th	e performan	ce describe	ed in Annex Z	A of the standard(s)

EN 54-17:2005+AC:2007 : Fire detection and fire alarm systems — Part 17: Short circuit isolators

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

## CONSTANCY OF PERFORMANCE OF THE CONSTRUCTION PRODUCT.

This certificate was first issued on 2022-07-07 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The attached annexes form part of this certificate.

Date of issue: 2022-07-07.

Steen Nilsson Responsible for evaluation

Merete Poulsen Responsible for certification decision



# Certificate No.: 8504-UKCA-CPR-UKCSP10118



Annex 1

#### EXTENT

Model reference: V-100 Base V-110 Base SIL2 V-120 Base SIL2 Ex ia

Full model codes are defined by the formats V-100/w, V-110/w and V-120/w where: w = Enabled options Blank = None, RETRO, CFxxx = Custom Features (C = A to Z, F = A to Z, xxx = 000 to 999)

### Conditions of use:

Suitable for indoor applications

## Performance

Essential characteristics	Clauses in EN 54-17:2005/AC:2007	Performance
Performance under fire conditions	5.21)	Pass
Operational reliability	4	Pass
Durability of operational reliability; temperature resistance	5.4, 5.5	Pass
Durability of operational reliability; vibration resistance	5.9 to 5.12	Pass
Durability of operational reliability; humidity resistance	5.6, 5.7	Pass
Durability of operational reliability; corrosion resistance	5.8	Pass
Durability of operational reliability; electrical stability	5.3, 5.13	Pass
1) This is assuming that the effect of th	he fire is to cause a short circuit in the tra	nsmission path that is protected by these
devices		





Annex 2

### TEST DOCUMENTATION

Accredited Laboratory	Report no.	Date
Intertek	103874656LHD-023	2020-03-20
Intertek	103874656LHD-030	2020-05-06
Intertek	103874656LHD-002c	2019-11-25

## **TECHNICAL BASIS**

	File Number	Title
BoM V-100		Bill of Materials Report
BoM V-110		Bill of Materials Report
BoM V-120		Bill of Materials Report



