

SYMPHONI LX WALL

Alarm units

Product Datasheet

EN 54-23 Coverage Reference: W-2.4-7.5

Features

- Ultra low current consumption
- 7.5m coverage (135m³)
- 0.5 or 1Hz flash rate
- IP21C protection
- Use where current consumption is a key consideration
- Ideal for bedrooms, bathrooms and toilets
- Switch flash rate to reduce current consumption
- External use in areas of high humidity

Description / Application

Its durable design ensures reliability and its high sound output makes it suitable for open areas or where there is higher than normal background noise.

The base is non-addressable. Optional colour: white or red.



| Product Name | Part number | Description |
|-------------------------|-------------------|-------------------------|
| Symphoni LX Wall, white | 116-4340-007.0008 | Symphoni LX Wall, white |
| Symphoni LX Wall, red | 116-4340-007.0009 | Symphoni LX Wall, red |

| Technical specifications | |
|--------------------------|---|
| Mounting Type | Wall |
| Voltage | 18 – 28Vdc (Fire Use) |
| Current | 15 – 30mA dependent on setting (Sounder and; tone 3) |
| Coverage (y) | 7.5m (Switchable to 2.5m) |
| Mounting Height (x) | 2.4m (max) |
| Coverage Volume Code | W-2.4-7.5 |
| Coverage Volume | 135 m ³ (15m ³) |
| Flash Rate | 1Hz (Switchable) |
| Operating Temperature | -25°C - +70°C |
| Monitoring | Reverse Polarity |
| Protection | IP21C |
| Weight | 200g |
| Body Colour | Red / white |
| Flash Colour | Red |
| Sound Output | 100dB(A) (Typical tone 29 – Symphoni) |

Dimension Drawing

